

**APSI500**  
ATX FONT



**CERTIFICATE** Compliant with ATX 12V standard / European engineering and internationally tested safety / Compliant with EU required directives and standards

**FAN** Ultra-Silent TACENS with smart thermal speed control and anti-vibration system 12cm /14 dB

**RAIL** Powerful single 12v

**SECURITY** Industrial-Grade electric protections and filtering for safest operation

**CABLES** Long cables for maximum case compatibility: 1x20+4pin, 1x12V 4+4pin, 3xSATA, 2XPATA

**DIMENSIONS** 150x85x140mm / 726g

| AC Input            | 200-240Vac |     | 4A   | 50-60Hz |       |
|---------------------|------------|-----|------|---------|-------|
|                     | +3.3V      | +5V | +12V | -12V    | +5Vsb |
| DC Output Voltage   | 24A        | 25A | 26A  | 0.5A    | 2.5A  |
| Max. Output Current | 180W       |     | 312W | 6W      | 12.5W |
| Combined Power      | 500W       |     |      |         |       |
| Total Power         | 500W       |     |      |         |       |

|              |                      |                    |            |
|--------------|----------------------|--------------------|------------|
| <b>MODEL</b> | <b>APSI500</b>       | <b>UNITS/BOX</b>   | <b>10</b>  |
| <b>EAN</b>   | <b>4718009156685</b> | <b>UNITS/PALET</b> | <b>400</b> |

